LATERAL CLEARANCE 3' MINIMUM FROM TRAVEL LANE. PLACE SIGN BEYOND SHOULDER SEE STANDARD POINT IF IT CANNOT BE INSTALLED **SPECIFICATIONS** PLUMB. IF SIGN IS PLACED WITHIN FOR APPROVED SIGN A LANE CLOSURE OR ON THE SUBSTRATE MATERIAL TRAVELWAY THE CLEARANCE APPLIES FROM THE OPEN LANE MOUNTING HEIGHT DIMENSIONS ROADWAY TO SIGN 1' MINIMUM. FOR INTERSTATE OR OTHER HIGH VOLUME ROADWAYS USE 5' MIN PAVED SHOULDER TRAVEL LANE SHOULDER POINT IF SUPPLEMENTAL PANEL IS REQUIRED USE A 5' MINIMUM HEIGHT TO MAIN SIGN WITH A 3' MINIMUM HEIGHT TO PANEL

GENERAL NOTES

- 1-DIMENSIONS SHOWN ARE MINIMUM VALUES. MOUNT SIGNS SO THEY WILL BE CLEARLY VISIBLE TO APPROACHING TRAFFIC EVEN WHEN SIGNS ARE MOUNTED BEHIND TRAFFIC CONTROL DEVICES SUCH AS DRUMS, BARRIER, OR OTHER OBJECTS,
- 2-ALL PORTABLE SIGNS AND STANDS MUST MEET OR EXCEED THE REQUIREMENTS OF NCHRP 350 FOR WORK ZONE CATEGORY II DEVICES. USE PORTABLE WORK ZONE SIGNS AND STANDS SPECIFICALLY DESIGNED FOR ONE ANOTHER.
- 3-ALL PORTABLE WORK ZONE SIGNS AND STANDS MUST BE LISTED ON NORTH CAROLINA'S APPROVED PRODUCTS LIST OR ACCEPTED AS TRAFFIC QUALIFIED BY THE WORK ZONE TRAFFIC CONTROL UNIT.

SHEET 1 OF 1

PORTABL ENGLISH

1110.02

ISION OF RALEIGH

CLEARANCE

HEIGHT

MOUNTING

SIGNS

ZONE ATERAL

FOR

DRAWING

STANDARD WORK